

# SC-11-1201-0001-04

## SmartCell Wireless Control Panel (No Comms Module) - German

### SmartCell overview

SmartCell has been designed as a complete wireless fire detection system to protect people and property. The system incorporates separate information zones which allow input devices to be configured in multiple configurations, providing maximum flexibility to the user and designer.

A SmartCell system can support up to 64 wireless devices consisting of 32 fire devices and 32 information devices.

Communication between devices and the control panel is bidirectional and operates in the European harmonised 868MHz frequency band.

With significant time saving against conventional and addressable fire system installations, no cables, no mess and no inconvenience to everyday business, SmartCell is perfect for all small to medium sized fire system installations.



### Details

- Fully wireless
- Quick and easy to install
- Compact enclosure
- 80 character OLED display
- Accommodates internal communications card for SmartCell Services connection
- 24 VDC version also available

# SC-11-1201-0001-04

## SmartCell Wireless Control Panel (No Comms Module) - German

### Technical specifications

---

#### General

---

User interface	16 zone indicators
Maximum system capacity (device count)	1 to 32

---

#### Electrical

---

Power supply type	230 VAC
Operating voltage	220 to 240 VAC, 50 Hz, 0.3 A
Current consumption	5 mA (PSU), plus 100 mA from control panel

---

#### Zone

---

Maximum zone capacity	up to 16
-----------------------	----------

---

#### Standby battery

---

Capacity	6 V 4 Ah
----------	----------

---

#### Physical

---

Form factor	Compact
Physical dimensions	275 x 220 x 80 mm (W x H x D)
Net weight	1.55 kg
Mounting type	Surface mount
Cable entries	4 x 100 mm (bottom) / 4 x 100 mm (back)

---

#### Environmental

---

Operating temperature	-5°C to +45°C
Storage temperature	0°C to +30°C
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP30

---

#### Regulatory

---

Compliance	CE
Certification	CPR
Standards	EN54-2 EN54-4 EN54-13 EN54-25

---

#### Wireless signalling

---

Operating frequency	868 to 870 MHz
Output transmitter power	14 dBm max. / 25 mW

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](http://firesecurityproducts.com) online or contact your sales representative.

Last updated on 31 October 2023 - 0:05