

## SC-33-0220-0001-99

### SmartCell White Sounder and Ceiling-Beacon (VAD White Flash)

#### Overview

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



#### **Details**

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

# SC-33-0220-0001-99 SmartCell White Sounder and Ceiling-Beacon (VAD White Flash)

#### **Technical specifications**

General	
Wireless frequency	868 MHz
Electrical	
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
Sounder	
Output level	92 dB(A) at 1 m max.
Output level adjustment	: High or low
Selectable tones	32
VAD	
Colour	white flash
Rating	C-3-12
Flash frequency	0.5 Hz (1 flash, every 2 seconds)
Physical	
Physical dimensions	110 x 79 mm (Ø x D)
Net weight	0.2 kg
Colour	White
Mounting type	Ceiling mount
Mounting position	Ceiling
Environmental	
Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries)
	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP21C
Regulatory	
Compliancy	CE
Certification	CPR
Standards	EN54-3
	EN54-13
	EN54-23 EN54-25
	LNJ4-ZJ



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.