

# SC-51-0300-0001-04

## **SmartCell Hausalarm Manual Call Point**

#### Overview

The SmartCell Hausalarm Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel. In some German applications, like smaller hotels, where the site is not connected to the ARC/Fire Brigade, a blue "Hausalarm" is used instead of the red Manual Call Point. This practice distinguishes between the red MCP which can be used for alerting the brigade and the blue "Hausalarm" which is used only for local alarms.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified to EN54-25 and compatible with the full SmartCell product range (EN54-11 certification is not applicable on "Hausalarm" because of the blue colour)

"Hausalarm" is for use only on sites which are not connected to Fire Brigade and require a localized alarm.



#### **Details**

- Quick and easy to install
- Blue Hausalarm for local alerts
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism

## SC-51-0300-0001-04 SmartCell Hausalarm Manual Call Point

### **Technical specifications**

| General               |   |
|-----------------------|---|
| Status indication     | LED   |
| Wireless frequency    | 868 MHz                                     |
| Compatibility         | SmartCell                                   |
| Electrical            |   |
| Batteries             | 2 x ER14505M 3.6 V lithium thionyl chloride |
|                       | batteries (Fanso or Titus)                  |
| Physical              |   |
| Physical dimensions   | 92 x 97 x 47 mm (W x H x D)                 |
| Net weight            | 0.2 kg                                      |
| Colour                | Blue (RAL 5005)                             |
| Mounting type         | Wall mount                                  |
| Environmental         |   |
| Operating temperature | -10 to +55°C                                |
| Storage temperature   | -10 to +55°C (without batteries)            |
| Relative humidity     | 95% noncondensing max.                      |
| Environment           | Indoor                                      |
| Regulatory            |   |
| Compliancy            | CE  |
| Certification         | CPR   |
| Certification marks   | EN54-25                                     |
| Standards             | EN54-25                                     |



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.