

SC-52-0200-0001-99 SmartCell Information Manual Call Point

Overview

The SmartCell Information Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel. The device when activated, sends an information alert to the Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- · Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism
- NOT FOR FIRE OR SECURITY APPLICATIONS

SC-52-0200-0001-99 SmartCell Information Manual Call Point

Technical specifications

General	
Status indication	LED
Wireless frequency	868 MHz
Compatibility	SmartCell
Electrical	
Batteries	2 x ER14505M 3.6 V lithium thionyl chloride
	batteries (Fanso or Titus)
Physical	
Physical dimensions	92 x 97 x 47 mm (W x H x D)
Net weight	0.2 kg
Colour	White
Mounting type	Wall mount
Environmental	
Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor
Regulatory	
Compliancy	CE
Certification	CPR
Standards	EN54-13
	EN54-25



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.