

Baseline product line

Hub Plus Jeweller

Control panel supporting Ajax wireless devices









Jeweller


communication technology

- Up to 2,000 m of radio communication in an open space
- Data is encrypted throughout the transmission process
- Auto adjustment of radio signal strength to reduce interference and devices' power consumption
- Regular polling to display current devices' statuses



Always online

- 4 communication channels: Ethernet, Wi-Fi, and 2 SIM cards that support 3G/2G
- The communication channels work simultaneously instant switch
- 99.99%¹ uptime of Ajax Cloud server



Features

- Up to 100 Ajax devices in the system
- Up to 32 automation scenarios
- Up to 25 cameras and DVRs²



Sabotage resistance

- Tamper alarm
- Notifications of jamming
- Detection of the connection loss with devices within 36 seconds³
- Up to 16 hours of battery life in case of power loss⁴

Quick installation and setup

- Connecting to Ajax apps via QR code
- Remote control and configuration in apps
- Effortless installation and replacement

Compliance with standards Communication Devices **Features** with Ajax devices Jeweller communication PD 6662:2017 Up to 100 Ajax wireless devices 50 users EN 50131 (Grade 2) Including up to 5 range extenders technology 32 automation scenarios and up to 10 sirens or keypads with 25 cameras and NVRs² a built-in siren 9 security groups Communication range 50 rooms up to 2,000 m In an open space Frequency bands 868.0-868.6 MHz Two-way communication between the hub and connected devices Additional features Power supply **Connection to CMS** Communication channels Main power supply unit SurGard (Contact ID) Over-the-air updates Ethernet, Wi-Fi, and 2 SIM cards: SIA (DC-09) 100-240 V, 50/60 Hz 2G GSM900/DCS1800 (B3/B8) Remote control and configuration ADEMCO 685 Backup power supply Other proprietary protocols in the app Built-in backup battery Li-Ion 2 A·h 3G WCDMA 850/900/2100 Types of notifications: SMS, calls, (B1/B5/B8)and push notifications Up to 16 hours of battery life in case of power loss4 **Enclosure** Installation Complete set **Hub Plus Jeweller** Colour Operating temperature range SmartBracket mounting panel from -10°C to +40°C white, black Power cable **Operating humidity Dimensions** Ethernet cable 163 × 163 × 36 mm Installation kit up to 75% SIM cards (depending on region) Quick start guide **Protection class** Weight IP50 350 g Tamper alarm

- 1 in 2023.
- 2 third-party cameras and DVRs.
- 3 depends on settings.
- 4 when only GSM works.













For detailed information, scan the QR code or follow the link: