

TSW100 INDUSTRIAL UNMANAGED POE+ SWITCH



FLYER // TSW100

TSW100 360° VIEW



Copyright © 2023, TELTONIKA NETWORKS. Specifications and information given in this document are subject to change by TELTONIKA NETWORKS without prior notice.

TELTONIKA | Networks


KEY FEATURES

HARDWARE

4-pin power socket, 7-58 VDC Idle: 2 W / Max (no PoE): 9 W / PoE Max: 129 W 802.3af/at (max 30 W per port, total power budget 120W* 5 x 10/100/1000 Ethernet ports: 4 x PoE, 1 x Uplink
802.3af/at (max 30 W per port, total power budget 120W*
5 × 10/100/1000 Ethernet ports: 4 × PoE_1 × Uplink
5 x Torroo Liternet ports. 4 x Foe, T x Opinik
10 x Ethernet, 1 x Power
IP30
-40 °C to 75 °C
Aluminium housing with wall or DIN rail mounting option and grounding capability
115 x 32 x 95 mm
340 g

PERFORMANCE SPECIFICATIONS

Bandwidth	10 Gbps
Packet buffer	128 KB
MAC address table size	2K entries
Auto MDI/ MDI-X Cable Detection	Yes



FRONT VIEW



BACK VIEW